




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | | |
|---|--|--|---|
| (51) International Patent Classification ⁷ : G01P 15/13, 15/08 | | A1 | (11) International Publication Number: WO 00/55638 |
| | | (43) International Publication Date: 21 September 2000 (21.09.00) | |
| (21) International Application Number: PCT/US00/40039 | | (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). | |
| (22) International Filing Date: 16 March 2000 (16.03.00) | | | |
| (30) Priority Data: 60/125,076 17 March 1999 (17.03.99) US | | | |
| (71) Applicant (for all designated States except US): INPUT/OUTPUT, INC. [US/US]; Suite 200, 12300 Charles E. Selecman Drive, Stafford, TX 77477 (US). | | | |
| (72) Inventors; and (75) Inventors/Applicants (for US only): SELYAKUMAR, Arjun [IN/US]; 4436 Jim West, Bellaire, TX 77401 (US). GOLDBERG, Howard, D. [US/US]; 3007 Colony Crossing, Sugar Land, TX 77479 (US). YU, Duli [CN/US]; 15700 Lexington Boulevard, #1301, Sugar Land, TX 77478 (US). IP, Matthew [-/US]; Austin, TX (US). SCHMIDT, Martin, A. [US/US]; 78 Ashley Place, Reading, MA 01867 (US). MARSH, James, L. [US/US]; 3305 Shimmering Dawn, San Antonio, TX 78253 (US). FUNG, Bing-Fai [-/US]; Austin, TX (US). SIMON, Philip [US/US]; Houston, TX (US). | | | |
| (74) Agents: MCCOMBS, David, L. et al.; Haynes and Boone, LLP, Suite 4300, 1000 Louisiana Street, Houston, TX 77002 (US). | | Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> | |

(54) Title: **SENSOR DESIGN AND PROCESS**

(57) Abstract

An accelerometer (305) for measuring seismic data. The accelerometer (305) includes an integrated vent hole for use during a vacuum sealing process and a balanced metal pattern for reducing cap wafer bowing. The accelerometer (305) also includes a top cap press frame recess (405) and a bottom cap press frame recess (420) for isolating bonding pressures to specified regions of the accelerometer (305). The accelerometer (305) is vacuum-sealed and includes a balanced metal pattern (730) to prevent degradation of the performance of the accelerometer (305). A dicing process is performed on the accelerometer (305) to isolate the electrical leads of the accelerometer (305). The accelerometer (305) further includes overshock protection bumpers (720) and patterned metal electrodes to reduce stiction during the operation of the accelerometer (305).